

Chapter 8

AADT: Annual Average Daily Traffic



AADT vs. ADT


AADT

Annual average daily traffic - taken over year and divided by the number of days within the year; normalizes seasonal, special event, and other fluctuations (used for crash analyses)

ADT


Average daily traffic - taken over a period of a few days or weeks; does not normalize seasonal, special event, and other fluctuations (NOT used for crash analyses)

AADT Data



TEAAS Resources and Information

Mileposting, TEAAS Links



Links and Information

[Bridge Document Management System \(BridgeDocs\)](#)

[County GIS Maps](#)

[Crash Rates](#)

[DMV CrashWeb](#)

[DMV CrashWeb Access North Carolina Identity Management Service \(NCID\)](#)

[DMV CrashWeb NCID New Account Instructions](#)

[DMV User Management Application \(UMM\)](#)

[Historical Roadway Characteristics Data \(MLI1\)](#)

[Information, Mapping, & Graphics \(IMG\)](#)

[List of County Information](#)

[MANTIS Bug Tracking System](#)

[NCDOT GIS Data Layers](#)

[NCDOT GIS Unit](#)

[Project Breakdown Maps](#)

[Project Search](#)

[Project Server \(bey let date\)](#)

[SR Number Lookup](#)

[TEAAS Website](#)

[TRACS Website](#)

[Volume \(AADT\) Maps](#)

<https://connect.ncdot.gov/resources/safety/Pages/TEAAS%20Information.aspx>

AADT Data (cont.)

- Mainline interstates, freeways, and major arterials are generally counted every year
- Collectors and most local routes are generally counted every other year
- Low volume local routes may never be counted and, therefore, their volumes may have to be estimated
- Municipal street volumes are usually not maintained by the NCDOT

AADT Data (cont.)

NCDOT NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
Connecting people and places safely and efficiently, with accountability and environmental sensitivity to enhance the economy, health and well-being of North Carolina.

Home | About | Careers | Contact | Search

NCDOT Mobile

Business | DMV | Newsroom | Programs | Projects | Travel & Maps

Travel & Maps

Traveler Information Management System

511 Information Line

Drive Green Save Green

Evacuation Maps

H.O.V. Lane Information

N.C. 12 Recovery Efforts

Incident Management Assistance Patrols

Maps & Publications

Road Rules

Safety Tips

Scenic Byways

State Mapping Resources

- Straightline Diagrams
- Traffic Volume Maps**
- Secondary Roads Lookup

Order Paper Maps

State Mapping FAQs

Twitter Updates

Snow Clearing Policy

Home » Travel & Maps » State Mapping Resources » Traffic Volume Maps

Traffic Volume Maps

Traffic Volume (AADT) Maps are a product created by the Traffic Survey Group in cooperation with the SRMU Mapping Section. The county and urban maps supplied by the mapping section serve as a foundation for Traffic Survey employees to identify locations known as "count stations". Traffic Surveys labels each of these stations with the **Annual Average Daily Traffic** counts. PDF's of the current AADT maps are available below.

If you are interested in learning more about Traffic Survey's mission, traffic data collection process and traffic data products, please visit their [website](#).

If you have further questions concerning Traffic Count Data Information, please contact the NCDOT Traffic Survey Group.

By clicking on the Traffic Volume Map links below, you can access the individual county sheets in PDF format. The name of the county will be followed by a number. These numbers represent each sheet, i.e., Sheet 2 of 9. If you do not know which sheet you need, click on the "sheet key". If a sheet key is not available, you can ALWAYS find a sheet key in the 1st sheet for each county.

Urban Area AADT Traffic Maps

To view available Urban AADT Maps, please click one of these links:

- Asheville
- Durham
- Greenville
- Rocky Mount
- Burlington
- Fayetteville
- Hickory
- Wilmington
- Chapel Hill
- Gastonia
- High Point
- Winston Salem
- Charlotte
- Goldsboro
- Jacksonville
- Concord & Kannapolis
- Greensboro
- Raleigh

[View All Available Urban Traffic Maps](#)

County Area AADT Maps by Year


To view available County AADT Maps, please click on of these links:

1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011

Urban AADT maps are available for the years 1997 through 2011 (depending on the urban area)


County AADT maps are available for the years 1999 through 2011

AADT Data (Cont.)



county map AADT counts (state-maintained roads only)

AADT Data (Cont.)




urban AADT counts (state-maintained roads + some local roads)

AADT Data (Cont.)

Traffic volumes tend to increase over time. Because traffic volumes are used to calculate crash rates, it is recommended that the median year's volume is used in crash analyses so that crash rates (CR) are not artificially inflated or deflated:

$$CR = \frac{\text{Crashes}}{\text{Exposure}}$$

Smaller volume in denominator can artificially increase the crash rate



$$Exposure = (volume)(distance)(time)$$

AADT Data (cont.)

- Used in calculating crash rates on the Intersection and Strip Analysis reports.
- Estimates the vehicle traffic through the study area
- Use the median year's AADT for a study.
- AADT data can be estimated by assuming an AADT growth rate of 3% per year.

NOTE: Only use AADT data from NCDOT Traffic AADT maps, volume counts, or some other accurate source!

AADT Data (cont.)

- For intersections, if the AADT for a leg is missing then the AADT from the opposite leg may be extended through the intersection
- If an AADT is not given, local knowledge can be used to estimate an AADT
- Growth rates other than the usual 2% and 3% may be used if based on other information or local knowledge
- A modification rate of ± 1.03 may be used instead of the adjustment formula

AADT Adjustment Formula

This formula is used if the AADT is not in the median year and the AADT needs to “grow” or “shrink” to the median year. Standard adjustment rates of 2% for rural locations and 3% for urban locations are used.

$$\text{Adjusted AADT} = \text{AADT} * \left(1 + \% \right)^n$$

Where:

n = Number of years (positive if adjusting up and negative if adjusting down)

% = adjustment rate (rural or urban)

AADT Adjustment Example

A study is being completed in a rural location with a date range of January 1, 2000 through December 31, 2002. The desired median year is 2001. However, the only AADT available is a 1999 AADT of 3,000 vehicles per day (VPD). The AADT would need to be adjusted for two years at a 2% growth rate:


$$\begin{aligned}\text{Adjusted AADT} &= 3,000 * \left(1 + 0.02 \right)^2 \\ &= 3121 \approx 3,100\end{aligned}$$

Intersection AADT Calculation

Calculate AADT for an intersection by:

- 1) Adding up the counts from all the legs
- 2) Dividing the total AADT by 2
(Done to counteract the fact that each vehicle passing through intersection is counted twice, once entering and once leaving)
- 3) Round the result (usually to the nearest hundred)

Intersection AADT Calculation Example




$$\begin{array}{r} 14,000 \\ 17,000 \\ 6,200 \\ + 2,500 \\ \hline 39,700 \end{array}$$


$$\frac{39,700}{2} = 19,850 \approx 19,900$$

Remember – if the AADT for a leg is missing then the AADT from the opposite leg may be extended through the intersection

Intersection AADT Calculation Exercise



Intersection AADT Calculation Exercise




$$\begin{array}{r} 2,000 \\ 5,000 \\ 2,000 \\ + 4,400 \\ \hline 13,400 \end{array} \quad \frac{13,400}{2} = 6,700$$

Strip AADT Calculation

- The AADT used for a strip location is a weighted average
- Calculate AADT for a strip by:
 - 1) Multiply the AADT counts along the strip by the distance that each AADT value represents
 - 2) Sum all of the AADT counts x distances
 - 3) Divide by the total length of the strip
 - 4) Round the result (usually to the nearest hundred)

Strip AADT Calculation Example


Calculate the 1998 AADT for this strip using 1997 AADT data



$$\begin{array}{rcl} .70 \text{ mi} * 1,900 & = & 1,330 \\ 1.20 \text{ mi} * 2,300 & = & 2,760 \\ 2.38 \text{ mi} * 1,200 & = & \underline{+ 2,856} \\ & & 6,946 \end{array} \Rightarrow \frac{6,946}{4.28} = 1,623$$


Update AADT to 1998 figures: $1623 * 1.03 = 1,672 \approx 1,700$

Strip AADT Calculation Exercise



Strip AADT Calculation Exercise

The total distance is 2.22 miles



$$\begin{array}{rcl} 1.14 \text{ mi} * 2,000 & = & 2,280 \\ 0.38 \text{ mi} * 1,300 & = & 494 \\ 0.70 \text{ mi} * 1,300 & = & + \quad 910 \\ & & \hline & & 3,684 \end{array}$$

$$\frac{3,684}{2.22} = 1,659$$

(round to either 1,700 or 1,650)